



# U661EA

## Roll Towel & Waste Combination Unit


Revision 11/14

JOB #:

ITEM #:

QUANTITY:

MOUNTING	HANDING	TYPE	SIZE	OTHER



### SPECIFICATIONS

**Body:** Fabricated of #22 ga stainless steel with a #4 satin finish.

**Flange:** Fabricated of #22 ga stainless steel finished to match cabinet with 1/4" returns. (No miters or welds)

**Cabinet Back:** Fabricated of stainless steel formed for rigidity with multiple welds to cabinet body.

**Cabinet Door:** Fabricated of #22 ga stainless steel with #4 satin finish, with full length door stop to reduce vandalism

**Towel Dispenser:** Roll towel mechanism is fabricated of #20 ga steel formed for rigidity. Unit will accommodate one 8" or 9" wide roll with a max O.D. of 7 7/8". Towel length dispensed has three adjustable settings. Battery operated sensor provides a hands free operation. (batteries not included)

**Removable Waste:** Fabricated of #22 ga stainless steel #4 satin finish with all leading edges to have a radius. Unit is secured in place by a bottom bracket guide and top lock. Embossed tabs allow liners to be held in place.

**Hinge:** Full length, heavy duty, stainless steel piano type hinge.

**Collars:** Fabricated of #22 ga stainless steel, finished to match cabinet.

**Overall Size:** 17 1/4"W x 54"H x 14 1/4"D  
**438mm x 1372mm x 362mm**

**Wall Opening:** 15 3/4"W x 52 1/2"H x 10"D  
**400mm x 1334mm x 254mm**

**Waste Capacity:** 13 gallons (1.74 cu ft)

**Towel Capacity:** One standard size roll of 8" or 9" wide. (Use only non-perforated towels). One stub roll up to 2 3/4" OD

**\*Recommended 600ft roll for best results.**

**Options:**

- VL1: Reusable vinyl liner

### INSTALLATION

Coordinate Installation with architect and contractor to avoid interference with pipes, vents, etc. Provide a rough wall opening 15 3/4"W x 52 1/2"H. Required wall depth, will depend if full or semi-recessing is required. If collar is required, slide collar over the back before installing into wall. Remove waste from cabinet and mount unit plumb and true in opening with proper fasteners per application. Secure waste in cabinet and load paper towels and batteries. Test unit for proper operation. Controls and or mechanisms should operate with one hand and force required to activate controls shelf be no greater than 5lbs. (4.27.4)

U661EA-S2: 2" Semi-Rec. collar, 8" wall opening, 203 mm  
 U661EA-S4: 4" Semi-Rec. collar, 6" wall opening, 152 mm  
 U661EA-S6: 6" Semi-Rec. collar, 4" wall opening, 102 mm  
 U661EA-SM: Full surface mounted collar.

### NOTES

Formerly Model #: U661/199EA